

TECHNICAL DATA SHEET**Adhertec 1795****PRODUCT DESCRIPTION**

Adhertec 1795 is a solventless hot melt rubber resin pressure sensitive adhesive. On reel, the ribbon is unrolled easily, because it is rolled with a paper lining treated with a silicone of high quality.

TECHNICAL DATA

Type:	Hot melt rubber resin
Colour:	Clear to light yellow
Total Thickness:	1/32" (0.8mm) or 1/64" (0.4mm)
Adhesive Thickness:	Not available
Peel adhesion:	700 oz/in (193 N/25 mm)
Elongation tensile:	Not available
U.V. Resistance:	No
Chemical resistance:	No
Application temperature: ..	> 10°C (> 50°F)
Heat resistance :	40°C (104°F)
Cold resistance:	0°C (32°F)
Density:	Not available
Storage:	2 years between 5°C and 25°C (2 years between 41°F and 77°F)

APPLICATION

Adhertec 1795 offers a superior bonding with plastics, metals, fabrics, and polyethylene sheeting.

CARACTERISTICS

- Clean, easy to use alternative to brush-on adhesives
- Aggressive rubber resin adhesive
- Permanently flexible
- It's offered in rolls of 66 yards (60 meters) long, rolled on a center of 3"
- Available in width of 1/2" (12.7mm), 3/4" (19mm), 1" (25.4mm), 1 1/2" (38mm) and 2 1/4" (57mm)

IMPORTANT NOTICE

All statements, recommendations and technical information contained in this document are based on tests and information which Tec-N-Tec believes to be accurate as of this date. The buyers however should test this product before use. Tec-N-Tec will assume no obligation or liability for results obtained from the use of this product.

The product and information herein are believed to be true. Tec-N-Tec Inc. will not be liable for any direct, indirect consequential economic or any other damage whatsoever, except to replace the product and or refund the purchase price to the purchaser.

8244 Pascal-Gagnon, Montreal Quebec, H1P 1Y4

Tel: 888-TEC-7777 Fax: 888-TEC-0282

Website: <http://www.tec-n-tec.com> E-Mail: pro@tec-n-tec.com