

TECHNICAL DATA SHEET**Adhertec DF236****PRODUCT DESCRIPTION**

Adhertec DF236 is a double coated tape with a high density crosslinked polyethylene foam, coated with a powerful rubber base adhesive.

TECHNICAL DATA

Type:	Double coated tape
Colour:	White
Total Thickness:	1/32" (0.8mm)
Adhesive Thickness:	4.5 mils (113µ)
Peel adhesion:	100 oz/in (28.3 N/25 mm)
Elongation tensile:	300 %
U.V. Resistance:	No
Chemical resistance:	Good
Application temperature: ..	4°C @ 38°C (40°F - 100°F)
Heat resistance :	82°C (180°F)
Cold resistance:	-18°C (0°F)
Density:	Not available
Storage:	2 years between 5°C and 25°C (2 years between 41°F and 77°F)

APPLICATION

Adhertec DF236 is used for sound and vibration dampening in business machines, industrial equipment, copy machines, electronic component packaging, glass panel mounts, seal, gasket, etc. Also, it can be use for mounting nameplates, signs, small die cast parts, mirrors, maps, etc. Finally, it can be used as gasketing and spacing.

CARACTERISTICS

- Offers a consistent quick stick and high shear.
- Good resistance to humidity, mild acids, oil and grease.
- Excellent conformability and compressability.
- Easily die cut.
- Adheres well to textured and irregular surfaces
- It's offered in rolls of 72 yards (66 meters) long, rolled on a center of 3 inches.
- Available in width of 2" 1/4 (57mm).

IMPORTANT NOTICE

All statements, recommendations and technical information contained in this document are based on tests and information which Tec-N-Tec believes to be accurate as of this date. The buyers however should test this product before use. Tec-N-Tec will assume no obligation or liability for results obtained from the use of this product.

The product and information herein are believes to be true. Tec-N-Tec Inc. will not be liable for any direct, indirect consequential economic or any other damage whatsoever, except to replace the product and or refund the purchase price to the purchaser.

8244 Pascal-Gagnon, Montreal Quebec, H1P 1Y4

Tel: 888-TEC-7777 Fax: 888-TEC-0282

Website: <http://www.tec-n-tec.com> E-Mail: pro@tec-n-tec.com